

```
/* Format string shown in the ActivityMonitor when fetching new mail. */
"ACTIVITY_FETCHING_NEW_MAIL_FORMAT" = "Scarico nuovi messaggi";

/* Format string shown in the ActivityMonitor when adding an email address to the address book. */
"ADDING_SENDER_TO_ADDRESSBOOK" = "Aggiungo %1$d di %2$d indirizzi e-mail alla Rubrica Indirizzi";

/* Format string shown in the ActivityMonitor when adding an email address to the previous recipients list. */
"ADDING_SENDER_TO_PREVIOUS_RECIPIENTS" = "Aggiungo %1$d di %2$d indirizzi e-mail all'Elenco destinatari precedenti";

/* Message shown in activity viewer when logging in securely to the POP server */
"POP_LOGGING_IN_FORMAT" = "Autentico come utente \"%@\";

/* Format string shown in the ActivityMonitor when appending messages to a mailbox. The first argument is the current message being transferred, the second is the total. */
"APPENDING_MESSAGES_FORMAT" = "Copio %1$d di %2$d messaggi";

/* String shown in the ActivityMonitor when appending a single to a mailbox. */
"APPENDING_SINGLE_MESSAGE" = "Copio messaggi";

/* Format string shown in the ActivityMonitor when saving a copy of a delivered message after delivery. The first argument is the mailbox name the message is being saved into. */
"ARCHIVING_MESSAGE_FORMAT" = "Archivio copia nella casella di posta \"%@\";

/* String used when displaying the Attachments header of a message in the main window. This value is only ever used for display and will not be part of any outgoing email. */
"Attachments" = "Allegati";

/* String used when displaying the Bcc header of a message in the main window. This value is only ever used for display and will not be part of any outgoing email. */
"Bcc" = "Bcc";

/* Format string shown in the ActivityMonitor when caching a message's attachments to disk. The first argument is the current message number, the second is the total number of messages. The third message is the subject of the message. */
"CACHING_MESSAGE_ATTACHMENTS_FORMAT" = "Conservo gli allegati per %1$d di %2$d: %3$@";

/* Format string shown in the ActivityMonitor when caching a message to disk. The first argument is the current message number, the second is the total number of messages. The third message is the subject of the message. */
"CACHING_MESSAGE_FORMAT" = "Conservo %1$d di %2$d: %3$@";

/* Format string shown in the ActivityMonitor when caching new messages to disk. */
"CACHING_MESSAGES_FORMAT" = "Conservo nuovi messaggi";

/* String used when displaying the Cc header of a message in the main window. This value is only ever used for display and will not be part of any outgoing email. */
"Cc" = "Cc";

/* Format for status string shown when changing flags for messages on an IMAP server. First argument is the number of messages, the second is a mailbox name. */
"CHANGING_MESSAGE_FLAGS_FORMAT" = "Modifico contrassegni per %1$d messaggi nella casella \"%2$@\";

/* Format for status string shown when changing flags for a single message on an IMAP server. Argument is a mailbox name. */
"CHANGING_SINGLE_MESSAGE_FLAGS_FORMAT" = "Modifico bandierine per il messaggio nella casella \"%@\";

/* Title of activity shown when Mail checks IMAP connections after the network configuration has changed. */
"CHECKING_CONNECTIONS_TASK_NAME" = "Verifico connessioni";

/* Status message shown when compacting multiple messages in a .mbox mailbox */
"COMPACTING_MESSAGES_FORMAT" = "Comprimo %1$d di %2$d messaggi...";

/* Status message shown when compacting a .mbox mailbox containing a single deleted message */
"COMPACTING_SINGLE_MESSAGE" = "Comprimo messaggio...";

/* Format string shown in the ActivityMonitor when configuring the headers of a message for delivery. */
"CONFIGURING_HEADERS_FORMAT" = "Configuro intestazioni posta";

/* Format string shown in the ActivityMonitor when connecting to a server. First argument is the hostname of the server (eg, 'mail.apple.com'), second is a positive integer, the IP port number (eg, 143) */
"CONNECTING_TO_SERVER_FORMAT" = "Connessione al server \"%@\";

/* Format string shown in the ActivityMonitor when copying a single message. */
"COPYING_MESSAGE_STATUS" = "Copio messaggio...";

/* Format string shown in the ActivityMonitor when copying messages. The argument is the number of messages being copied. */
"COPYING_MESSAGES_FORMAT" = "Copio %d messaggi...";

/* Format string shown in the ActivityMonitor when creating a new IMAP mailbox on the server. Argument is a mailbox name. */
"CREATING_MAILBOX_ON_SERVER_FORMAT" = "Creo nuova casella \"%@\";

/* String used when displaying the Date header of a message in the main window. This value is only ever used for display and will not be part of any outgoing email. */
"Date" = "Data";

/* Format string shown in the ActivityMonitor when deleting an IMAP mailbox on the server. Argument is a mailbox name. */
"DELETING_MAILBOX_ON_SERVER_FORMAT" = "Cresco nuova casella \"%@\";

/* Activity viewer string that shows up when the user is transferring messages */
"DELETING_MESSAGES" = "Elimino messaggi";

/* Title of activity when the user deletes some messages from a mailbox. */
"DELETING_MESSAGES_TASK_NAME" = "Elimino Messaggi";

/* Format of title of activity in the ActivityMonitor when deleting messages older than a certain number of days from the the junk mailbox. The argument is the number of days, and is greater than zero. */
"DELETING_OLD_JUNK_MANY_DAYS_FORMAT" = "Cancello Posta indesiderata più vecchia di %d giorni";

/* Title of activity in the ActivityMonitor when deleting messages older than a certain number of days from the junk mailbox. The argument is the number of days */
"DELETING_OLD_JUNK_ONE_DAY" = "Cancello messaggi indesiderati più vecchi di un giorno";

/* Format of title of activity in the ActivityMonitor when deleting messages older than a certain number of days from the the sent messages mailbox. The argument is the number of days, and is greater than zero. */
"DELETING_OLD_SENT_MESSAGES_MANY_DAYS_FORMAT" = "Cancello copie di messaggi inviati da più di %d giorni";

/* Title of activity in the ActivityMonitor when deleting messages older than a certain number of days from the sent messages mailbox. The argument is the number of days */
"DELETING_OLD_SENT_MESSAGES_ONE_DAY" = "Cancello copie di messaggi inviati da più di 1 giorno";

/* Format of title of activity in the ActivityMonitor when deleting messages older than a certain number of days from the trash. The argument is the number of days, and is greater than zero. */
"DELETING_OLD_TRASH_MANY_DAYS_FORMAT" = "Cancello posta eliminata da più di %d giorni";

/* Title of activity in the ActivityMonitor when deleting messages older than a certain number of days from the trash. The argument is the number of days */
"DELETING_OLD_TRASH_ONE_DAY" = "Cancello posta eliminata da più di un giorno";

/* Status message that indicates we are delivering a message. */
"DELIVERY_MESSAGE_STRING" = "Invio messaggio";

/* Title of the special top-level Drafts container. This is a UI element only, no actual mailbox will have this name */
"Drafts" = "Drafts";
```

```
"DRAFTS_SPECIAL_MAILBOX_NAME" = "Bozze";

/* Title string for Enter Password dialog box. Argument is the name of the account. */
"ENTER_PASSWORD_ACCOUNT_TITLE" = "Introduci la password per l'account \"%\";

/* Title string for Enter Password dialog box when no account is specified. */
"ENTER_PASSWORD_TITLE" = "Inserisci Password";

/* Message shown in activity viewer while we are figuring out what rules apply to the messages */
"EVALUATING_RULES_FORMAT" = "Valuto messaggio %1$d di %2$d";

/* Message displayed in status line when preparing to fetch headers from IMAP server. */
"FETCHING_HEADERS" = "Scarico intestazioni...";

/* Format string shown in the ActivityMonitor when we are done with an activity. */
"FINISHED_ACTIVITY_FORMAT" = "Fine. ";

/* The name of the smart mailbox that holds flagged messages. */
"FLAGGED_SMART_MAILBOX" = "Contrassegnato";

/* Prefix for the subject of a forwarded message. This string will be used when displaying the subject of the message in the main window's message list as well as in
the message viewer. It will not be used when actually sending mail because most other clients do not support localized prefixes. */
"FORWARD_SUBJECT_PREFIX" = "I:";

/* String used when displaying the From header of a message in the main window. This value is only ever used for display and will not be part of any outgoing email. */
"From" = "Da";

/* Format string shown in the ActivityMonitor when getting the list of child mailboxes from the file system. */
"GATHERING_CHILDREN_FROM_DISK_FORMAT" = "Raccolgo dal disco gli elementi secondari per l'account locale";

/* Format string shown in the ActivityMonitor when getting the unread count for a mailbox. */
"GET_UNREAD_COUNT_FORMAT" = "Scarico elenchi non letti per la casella \"%\";

/* Format string shown in the ActivityMonitor when getting unread counts from an IMAP server. */
"GET_UNREAD_COUNTS_FORMAT" = "Scarico elenchi non letti";

/* Format string shown in the ActivityMonitor when getting a message's headers from an IMAP server. */
"GETTING_HEADERS_FORMAT" = "Ricevo intestazioni messaggi dal server";

/* Format string shown in the ActivityMonitor when getting the list of mailboxes from an IMAP server. */
"GETTING_MAILBOX_HIERARCHY_FORMAT" = "Esamino la gerarchia delle caselle";

/* Format string shown in the ActivityMonitor when getting a message body from an IMAP server. */
"GETTING_MESSAGE_BODY_FORMAT" = "Scarico corpo del messaggio dal server";

/* Title of activity which changes IMAP message flags (read/unread, status, flagged) */
"IMAP_CHANGING_FLAGS_TASK_NAME" = "Modifico contrassegni";

/* Status message shown when compacting messages in a IMAP mailbox. */
"IMAP_COMPACTING_STATUS" = "Comprimo messaggi sul server...";

/* Status message when we're first opening a mailbox on an IMAP server. */
"IMAP_COMPARING_NOTES" = "Confronto note con il server...";

/* Format of status string when connecting to an account. Argument is the server hostname. */
"IMAP_CONNECTING_FORMAT" = "Connessione al server \"%\";

/* Title of activity launched when the user disables/deletes an account, or at quit time. Argument is the hostname of an IMAP server. */
"IMAP_LOGGING_OUT_TASK_NAME_FORMAT" = "Eseguo il logout dal server \"%\";

/* Status message shown when cleaning up old IMAP message files from disk. */
"IMAP_Removing_CACHE_FILES" = "Rimuovo i documenti obsoleti dalla cache...";

/* Message shown in the ActivityMonitor when opening the new Address Book for the first time and items from the old address book get imported. */
"IMPORTING_OLD_ADDRESS_BOOK" = "Importo dati rubrica indirizzi esistente";

/* Title of the special top-level Inbox container. This is a UI element only, no actual mailbox will have this name */
"INBOX_SPECIAL_MAILBOX_NAME" = "Entrata";

/* Format string shown in the ActivityMonitor when incorporating messages from a spool file on disk to a mailbox. */
"INCORPORATING_MESSAGES_FORMAT" = "Incorpora messaggi dal documento di spool";

/* Name of the mailbox for messages that have been marked as being junk mail */
"JUNK_MAIL_MAILBOX_NAME" = "Indesiderata";

/* Title of the special top-level Junk Mail container. This is a UI element only, no actual mailbox will have this name */
"JUNK_SPECIAL_MAILBOX_NAME" = "Indesiderata";

/* Name of activity (as shown in Activity Viewer window) which read's the user's address book information soon after Mail launches. */
"LOADING_ADDRESS_BOOK" = "Carico Rubrica Indirizzi";

/* Format string shown in the ActivityMonitor when searching for an image of a message's sender. */
"LOOKING_FOR_SENDER_IMAGE" = "Cerco immagine mittente";

/* Format for displaying a mailbox name, for example in status text. First argument is the last component of the mailbox's name (eg, \"Sent\"), second is the mailbox's
account name or hostname (eg, \"Work\", or \"mail.mac.com\"). */
"MAILBOX_DISPLAY_FORMAT" = "%1$@ - %2$@";

/* Format for alert shown when a message can't be delivered because its size exceeds the maximum an SMTP server allows. Arguments are both localized strings
representing the message size and the max allowed size (eg, in English, '5 MB'). */
"MESSAGE_TOO_LARGE" = "Le dimensioni del tuo messaggio sono %1$@ ed eccedono il limite massimo concesso dal server, pari a %2$@.

/* Title of activity in the ActivityMonitor when deleting all the messages in the trash for a particular account. The argument is the name of the account. */
"MF_DELETING_TRASH_FOR_ACCOUNT" = "Elimino Messaggi indesiderati per l'account \"%\";

/* Name of account for the users primary mac.com account (the one setup in Internet System Preferences) */
"MY_ITOOLS_ACCOUNT" = "Il mio account .Mac";

/* Error message reported when the user cancels a login password panel. */
"NO_PASSWORD_PROVIDED_ERROR" = "Nessuna password indicata. ";

/* Error message reported when the user cancels a login password panel. The first argument is the user name and the second is the server name. */
"NO_PASSWORD_PROVIDED_FOR_USER_FORMAT" = "Nessuna password fornita all'utente \"%1$@\" sul server \"%2$@\";

/* String fragment shown in status message when the message being indexed doesn't specify a subject string. */
"NO SUBJECT" = "Senza oggetto";

/* Format for status message shown when a mailbox is being opened. */
"OPENING_MAILBOX" = "Apro casella...";

/* Title of the special top-level Outbox container. This is a UI element only, no actual mailbox will have this name */
"OUTBOX_SPECIAL_MAILBOX_NAME" = "Uscita";
```

```
/* Message shown on panel when prompting the user for a password. First argument is the account's username, the second is the account type (IMAP, SMTP, iTools or POP), the third is the hostname of the server (like mail.mac.com). */
"PASSWORD_MESSAGE_FORMAT" = "Inserisci la password per l'utente \"%1$@\" sul %2$@ server \"%3$@\";

/* Message shown in activity viewer while we are actually performing rule actions */
"PERFORMING_MESSAGE_ACTION" = "Eseguo azioni regole";

/* Title of activity in the ActivityMonitor when resuming a previously pended operation like an append that happened while offline. */
"PERFORMING_PENDED_OPERATIONS_TASK_NAME" = "Eseguo operazioni sospese";

/* Name of account containing on-disk mailboxes (as opposed to POP or IMAP). */
"PERSONAL_MAILBOXES" = "Sul mio Mac";

/* Warning text shown in a panel if a message is larger than the size set in the preferences, indicating, in order, the size (a localized string), the sender and subject. It gives the user the options to download, skip, or immediately delete the message. It also informs the user if no choice is made within 15 seconds, it will be downloaded. */
"POP_BIG_MESSAGE_WARNING_FORMAT" = "Hai ricevuto un messaggio %1$@ da %2$@ riguardante \"%3$@\".\n\nLo puoi scaricare adesso, rimandare la ricezione fino alla prossima volta in cui eseguirai Mail o eliminarlo definitivamente dal server senza aprirlo. Se non effettuerai una scelta entro 15 secondi, il messaggio verrà scaricato.';

/* Message shown in activity viewer while we check for messages that need to be downloaded */
"POP_CHECKING_MESSAGES" = "Scarico messaggi...";

/* Message shown in activity viewer when we are closing the connection to the server */
"POP_CLOSING_CONNECTION" = "Chiudo la connessione al server...";

/* Message of POP fetch progress panel showing message being deleted */
"POP_DELETING_MESSAGE_FORMAT" = "Elimino messaggio %1$d: %2$@";

/* Message of POP fetch progress panel showing how many messages have been fetched out of a total */
"POP_FETCHING_MESSAGES_WITH_TOTAL_FORMAT" = "Scarico %1$d di %2$d: %3$@";

/* Message shown in activity viewer while figuring out what messages the user has not yet received from the server */
"POP_FINDING_UNSEEN_MESSAGES" = "Trovo messaggi non letti...";

/* Message shown in activity viewer when logging in to the POP server */
"POP_LOGGING_IN_FORMAT" = "Eseguo il login come utente \"%@\";

/* Message shown in activity viewer after finding messages that need to be downloaded but before the actual downloading has begun */
"POP_PREPARING_TO_FETCH" = "Preparo scaricamento messaggi...";

/* Message shown in activity viewer when removing messages that were fetched from the POP server. */
"POP_Removing_MESSAGES" = "Rimuovo messaggi dal server...";

/* Message shown in activity viewer when removing messages that we fetched from the POP server. Arguments are the number of the message being deleted and the total number of messages to delete. */
"POP_Removing_MESSAGES_FORMAT" = "Rimuovo messaggio %1$d di %2$d";

/* Message shown in activity viewer when sending the users password to the POP server */
"POP_SENDING_PASSWORD" = "Invio password...";

/* Message of POP fetch progress panel showing message being skipped */
"POP_SKIPPING_MESSAGE_FORMAT" = "Ignoro messaggio %1$d: %2$@";

/* Format string shown in the ActivityMonitor when reading the mbox file. */
"READING_MAILBOX_FILE_FORMAT" = "Leggo documento di casella di posta...";

/* Format string shown in the ActivityMonitor when reading a table of contents. */
"READING_TABLE_OF_CONTENTS_FORMAT" = "Leggo indice...";

/* Format string shown in the ActivityMonitor when reapplying sorting rules. */
"REAPPLY_SORT_RULES_FORMAT" = "Reindirizzo messaggi...";

/* Format string shown in the ActivityMonitor when rebuilding a mailbox. */
"REBUILDING_MAILBOX_FORMAT" = "Ricostruisco...";

/* Format string shown in the ActivityMonitor when rebuilding the table of contents for a Personal Mailbox. The first argument is percentage done. */
"REBUILDING_TOC_FORMAT" = "Ricostruisco indice... (%d%% ricostruito)";

/* Format for status string used when fetching an unknown number of messages from the IMAP server. */
"RECEIVED_HEADERS_FORMAT" = "%d intestazioni ricevute...";

/* Format for status string shown when fetching a known number of headers from the IMAP server. */
"RECEIVED_HEADERS_WITH_TOTAL_FORMAT" = "%1$d di %2$d intestazioni ricevute...";

/* Message shown on panel when prompting the user for a password. First argument is the account type (IMAP, SMTP, iTools or POP), the second is the hostname of the server (like mail.mac.com), and the third is the account's username. */
"REENTER_PASSWORD_MESSAGE_FORMAT" = "Il server %1$@ \"%2$@\" ha respinto la password per l'utente \"%3$@\".\n\nInserisci di nuovo la password o annulla.';

/* Format string shown in the ActivityMonitor when removing attachment files off disk. */
"REMOVING_ATTACHMENTS_FORMAT" = "Rimuovo allegati messaggio...";

/* String used when displaying the Reply-To header of a message in the main window. This value is only ever used for display and will not be part of any outgoing email. */
/* "Reply-To" = "Rispondi a"; */

/* Prefix for the subject of a message which is a reply to another message. This string will be used when displaying the subject of the message in the main window's message list as well as in the message viewer. It will not be used when actually sending mail because most other clients do not support localized prefixes. */
"REPLY SUBJECT PREFIX" = "Re:...";

/* String used when displaying the Resent-Cc header of a message in the main window. This value is only ever used for display and will not be part of any outgoing email. */
/* "Resent-Cc" = "Rinvia-Cc"; */

/* String used when displaying the Resent-From header of a message in the main window. This value is only ever used for display and will not be part of any outgoing email. */
/* "Resent-From" = "Rinvia-Da"; */

/* String used when displaying the Resent-To header of a message in the main window. This value is only ever used for display and will not be part of any outgoing email. */
/* "Resent-To" = "Rinvia-A"; */

/* Format string shown in the ActivityMonitor when completing a previously incomplete append of messages to a mailbox. */
"RESUMING_INTERRUPTED_APPEND_FORMAT" = "Riprendo operazione sospesa...";

/* Title of entry in the Activity Viewer for tasks that route messages between mailboxes */
"ROUTING_MESSAGES" = "Indirizzo messaggi...";

/* Message shown in Activity Viewer when saving the address book after importing. */
"SAVING_IMPORTED_ADDRESS_BOOK" = "Registro in Rubrica Indirizzi...";

/* Format string shown in the ActivityMonitor when saving the table of contents of a mailbox to disk. */
"SAVING_TOC_FORMAT" = "Registro indice...";
```

```
/* Format string shown in the ActivityMonitor when sending a message. The argument is the subject of the message being sent. */
"SEND_MESSAGE_FORMAT" = "Invio messaggio: %@";

/* Format string shown in the ActivityMonitor when sending data to a server. The argument is the percentage of the data we've sent so far. */
"SENDING_DATA_FORMAT" = "Invio dati (%d% inviato)";

/* Format string shown in the ActivityMonitor when sending the list of recipients to an SMTP server while delivering a message. */
"SENDING_RECIPIENTS_FORMAT" = "Invio destinatari";

/* Title of the special top-level Sent container. This is a UI element only, no actual mailbox will have this name */
"SENT_MESSAGES_SPECIAL_MAILBOX_NAME" = "Inviata";

/* String used when displaying the Subject header of a message in the main window. This value is only ever used for display and will not be part of any outgoing email.
*/
"Subject" = "Oggetto";

/* Status message shown in the activity viewer when registering with the Sync Services (at launch or when changing the Sync Prefs in the General Pref Pane). */
"SYNC_STATUS_REGISTERING" = "Registro le preferenze di sincronizzazione .Mac";

/* Status message shown in the activity viewer while syncing (iSync). */
"SYNC_STATUS_SYNCING" = "Sincronizzo";

/* Title of task which synchronizes an IMAP mailbox with the server. Argument is the mailbox name. */
"SYNCHRONIZING_MAILBOX_STATUS_FORMAT" = "Sincronizzo %@",

/* Title of task which synchronizes one or IMAP mailboxes with the server. */
"SYNCHRONIZING_MAILBOXES_TASK_NAME" = "Sincronizzo caselle postali";

/* Format string shown in the ActivityMonitor when synchronizing the list of mailboxes with the filesystem. */
"SYNCHRONIZING_WITH_FILE_SYSTEM_FORMAT" = "Sincronizzazione con file system";

/* Format string shown in the ActivityMonitor when synchronizing an IMAP mailbox with the server. */
"SYNCHRONIZING_WITH_SERVER_FORMAT" = "Sincronizzazione con il server";

/* String used when displaying the To header of a message in the main window. This value is only ever used for display and will not be part of any outgoing email. */
"To" = "A";

/* Activity viewer string that shows up when the user is transferring messages */
"TRANSFERRING_MESSAGES" = "Copia messaggi";

/* Title of the special top-level Trash container. This is a UI element only, no actual mailbox will have this name */
"TRASH_SPECIAL_MAILBOX_NAME" = "Cestino";

/* Status message shown when cleaning up old IMAP message files from disk. */
"UPDATING_CACHE_STATUS_MESSAGE" = "Aggiorno directory cache";

/* Format string shown in the ActivityMonitor when updating the junk mail status for messages. The first argument is the current message number, the second is the total number of messages. */
"UPDATING_JUNK_MAIL_LEVEL_FORMAT" = "Aggiorno lo stato della posta indesiderata per il messaggio %1$d di %2$d";

/* Format string shown in the ActivityMonitor updating message colors. The first argument is the current message number, the second is the total number of messages. */
"UPDATING_MESSAGE_COLOR_FORMAT" = "Aggiorno il colore per il messaggio %1$d di %2$d";

/* Format string shown in the ActivityMonitor when updating message colors. */
"UPDATING_MESSAGE_COLORS" = "Aggiorno colori messaggio";

/* Format string shown in the ActivityMonitor updating number of attachments. The first argument is the current message number, the second is the total number of messages. */
"UPDATING_NUMBER_OF_ATTACHMENTS_FORMAT" = "Aggiorno il numero di allegati per il messaggio %1$d di %2$d";

/* Format string shown in the ActivityMonitor at the end of making offline changes. */
"UPDATING_OFFLINE_CACHE_STATUS" = "Aggiorno buffer scollegata";

/* Format string shown in the ActivityMonitor when waiting for a connection to the server. */
"WAITING_FOR_CONNECTION_FORMAT" = "Attendo l'apertura della connessione...";

/* Format string shown in the ActivityMonitor when writing changes to disk. */
"WRITING_CHANGES_TO_DISK_FORMAT" = "Registro le modifiche sul disco";

/* Status message shown in the activity viewer while saving message changes to disk. Arguments are index of the current message being saved and the total number of messages being saved. */
"WRITING_CHANGES_TO_DISK_PROGRESS_FORMAT" = "%1$u di %2$u messaggi";
```